

WEV 15-125 Quick (600468000) Angle Grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600468000
EAN 4007430243751



Product may differ from Image



- Highest service life for extreme applications: robust, powerful angle grinder with speed control and greatest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

Grinding wheel Ø	125 mm / 5 " "
Rated input power	1550 W
Output power	940 W
No-load speed	2800 - 11000 rpm
Revolutions at rated load	11000 rpm
Torque	3.5 Nm / 31 in-lbs in-lbs
Spindle thread	M 14
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	4 m / 13 ft

Vibration

Surface grinding	6 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	3.6 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard
Metabo VibraTech (MVT) side handle
Inner support flange
M-Quick flange nut