

KH 5-40 (600763610) Combination Hammer Plastic Carry Case

Order no. 600763610
EAN 4007430331854



Product may differ from Image



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life

Technical data

Characteristics

Max. single blow energy (EPTA)	7.1 J
Maximum impact rate	2800 bpm
Rated input power	1100 W
Drill-Ø concrete with hammer drills	40 mm / 1.6 " mm
Drill-Ø masonry with core bits	105 mm / 4 1/8 "
No-load speed	620 rpm
Bit retainer	SDS-max
Collar diameter	61 mm / 2.4 " mm
Weight (without power cable)	7.1 kg
Cable length	4 m

Vibration

Hammer drilling concrete	16.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	13.3 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	95 dB(A)
Sound power level (LWA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

rubber-coated side handle
Plastic carry case
Drilling depth guide
Lubricant for tool shank end