

**WF 18 LTX 125 Quick (601306840) Cordless Flat-head Angle Grinder  
18V ; MetaLoc**

Order no. 601306840  
EAN 4007430287182



Product may differ from image



- Extremely flat gear head permits working within acute angles down to 43°
- Compact design for quick removal of welding slag, rust or paint in tight places e.g. frame constructions
- Low-fatigue working even on weld seams in difficult to access places thanks to slim handle
- Robust motor for long service life
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better working in hard to reach places
- Detachable dust filter protects motor from coarse particles
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.
- Battery packs with capacity display for checking the charge status

**Technical data****Characteristics**

|                                 |                  |
|---------------------------------|------------------|
| Battery voltage                 | 18 V             |
| Minimum accessible angle        | 43 °             |
| Grinding wheel Ø                | 125 mm / 5 "     |
| No-load speed                   | 8000 rpm         |
| Spindle thread                  | M 14             |
| Weight (including battery pack) | 2.4 kg / 5.3 lbs |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 83 dB(A) |
| Sound power level (LwA)      | 94 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

**Scope of delivery**

5 Flap discs Flexiamant Super Convex (125mm; P60)  
Quick-locking nut  
Side handle  
Dust protection filter  
MetaLoc case  
without battery pack, without charger  
Guard  
Inner support flange