

**STA 18 LTX 140 (601405500) Cordless Jigsaw**  
18V 2x4Ah Li-ion; Charger ASC 55 (220-240 V / ); Plastic Carry Case

Order no. 601405500  
EAN 4007430213686



Product may differ from Image



- Extremely powerful jigsaw with VTC-Electronics for fast cuts into softwood of up to 140 mm
- High sawing performance: in excess of 40 metres in chipboard (19 mm) with only one battery pack charge
- Extremely handy due to small handle size and soft-grip surface
- Precise and material-matched sawing due to the variable stroke rate, pendulum stroke and low-lying saw blade guidance with spring support
- Metabo "Quick" for changing saw blades without tools and with automatic ejection
- Convenient automatic start-up with automatic stroke rate acceleration
- Simple bevel cuts thanks to footplate with rest points that can be adjusted without tools
- Selectable shaving blower function ensures free view of cutting line
- Integrated LED work light for illumination of the cutting line
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised stroke rates, which remain constant under load
- Restart protection: prevents unintentional start-up after battery pack change
- Long service life thanks to optimum gear and motor design and robust die-cast aluminium gear housing
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

## Technical data

### Characteristics

Type of battery pack	Li-ion
Battery pack capacity	2 x 4 Ah
Battery voltage	18 V
Cutting depth wood	140 mm / 5 1/2 "
Cutting depth NF metal	35 mm / 1 3/8 "
Cutting depth sheet steel	10 mm / 3/8 "
Swivel range from / to:	- 45 / + 45 °
Pendulum stroke levels	4
Strokes in idle	1000 - 3000 rpm
Weight (including battery pack)	2.9 kg / 6.4 lbs

### Vibration

Sawing wood	12 m/s <sup>2</sup>
Sawing metal	12 m/s <sup>2</sup>
Uncertainty of measurement K	2.3 m/s <sup>2</sup>

### Noise emission

Sound pressure level	90 dB(A)
Sound power level (LwA)	101 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Extraction nozzle  
 Chip guard plate  
 2 Li-Power battery packs (18 V/4.0 Ah)  
 Charger ASC 55 "AIR COOLED"  
 Plastic carry case  
 Protective glass  
 Plastic guard plate