

Insulation stripper for special applications



Art. No. 708 200 3

- Special hand tool with length stop for high-quality stripping and dismantling of single and multi-wire cables ranging from 0.03 to 16 mm²
- Applicable for a great variety of insulations of differing hardness
- No pinching or deforming of cable ends, thanks to a special cutting mode
- blades for different wire ranges
- Customized blade designs on request
- Automatic release after operation



Position cable at length stop



Stripping with profile blades



Automatic removal of insulation

Art. No.

Range of applications







Capacity




Strip dimensions

mm

Stripper plate pairs

Art. No.	Range of applications	Capacity	Strip dimensions mm	Stripper plate pairs
----------	-----------------------	----------	------------------------	----------------------

Art. No.	Range of applications	Capacity	Strip dimensions mm	Stripper plate pairs
708 201 3	Tool for PTFE insulated cables with cable guide	0,03 - 2,08 mm ²	Ø 0.35 / Ø 0.55 Ø 0.80 / Ø 1.05 Ø 1.35 / Ø 1.60 Ø 1.75	
708 202 3	Tool for hybrid cables	max. Ø 6,9 mm CU 1,5 mm ²	Ø 5.70 Ø 1.60	
708 203 3	Tool for PTFE insulated cables	2,5 - 10 mm ²	Ø 4.45 Ø 3.50 Ø 2.70 Ø 2.30	
708 204 3	Tool for PTFE insulated cables and high-voltage cables	0,5 / 2,5 / 16 mm ²	Ø 5.70 Ø 2.30 Ø 1.00	
708 205 3	Tool for DIN-standard multi-wire cables	0,14 - 6 mm ²	Ø 0.70 / Ø 1.35 Ø 1.70 / Ø 2.30 Ø 2.70 / Ø 3.50	
708 206 3	Tool for 1, 2 and 4-core POF-cables	1-adrig Ø 6,7 mm 2-adrig Ø 6,2 mm 4-adrig Ø 5,5 mm Ø 2,2 mm POF	Ø 5.80 Ø 4.80 Ø 2.50 Ø 1.50	

Art. No.	Range of applications	Capacity	Strip dimensions mm	Stripper plate pairs
708 207 3	Tool for hybrid cables and matching POF and copper braid cables	Ø 6,9mm 1,5 mm ² Ø 2,2 mm POF	Ø 5.65 Ø 1.20 Ø 1.80	
708 208 3	Tool for 10-wire ribbon cable	0,08 mm ² AWG 28	parallel slot 0,40	
708 209 3	Tool for solar cable "RADOX® 125"	2,5 / 4,0 / 6 mm ²	Ø 3.90 Ø 3.00 Ø 2.40	
708 210 3	Tool for Cu single wire cable	10 mm ²	Ø 4.00	